



# E2460SD2

24

(61) LCD MONITOR

The 24-inch E2460SD2 display features Full HD resolution for detailed imagery and a fast 1ms response time that makes it suitable even for games or movies. Standard VGA and DVI-D connectors and the VESA mount make this monitor ideal for a variety of office and home users.



Vesa Wallmount



## 1ms Response Time

A pixel response time of 1ms GTG means speed without the smear for an enhanced experience.

Fast-moving action and dramatic transitions will be rendered smoothly without the effects of ghosting.




## Kensington Lock

Kensington Lock is an anti-theft system, comprising a metal-reinforced hole in the body of the respective device, to use with a metal cable secured with a key/lock system. Kensington locks enable you to secure your AOC monitor during a LAN event, an organisation, or wherever you carry it.



## Vesa Mount

AOC's Ergo Base stands bring versatility, sturdiness and ease of use in one package. But do you still want to use your wall mount or multi-monitor setup using desk mounts? VESA mounts bring you the uppermost flexibility. Upside-down, in pivot mode, on top of each other, attach your monitor wherever you want using 3<sup>rd</sup> party mounts and stands thanks to the VESA mount option.



## LED-backlight

AOC's monitors use LED backlights with white LEDs to illuminate the display panel (TN, IPS or VA). Compared to old backlights using CCFL, LED backlights have much lower energy consumption and more dimming control over the brightness, and contribute to the thinness of the display.

Screen Details

Color	Black
Resolution	1920x1080 PX
Refresh rate	60Hz
Response time	1
Panel	TN
Backlight	WLED
Aspect ratio	16:9
Brightness (typical)	250
Contrast (dynamic)	20M:1
Contrast (static)	1000:1
Pixel Pitch (H) (V)	276
Diagonal (inch)	24
Active Screen Area (HxW)	531.36x298.89 mm
Viewing angle (CR10)	170/160 °
Display Colours	16.7 Million
OSD languages	EN, FR , ES, PT, DE, IT, NL, SE, FI, PL ,CZ, RU, KR, CN (T), CN (S), JP

Connections

Signal Input	VGA, DVI
--------------	----------

What's in the box

VGA cable (1,2 m), DVI cable (1,5 m), Power Cable C7 (1.2 m),
---

Sustainability

- Environmental and energy: RoHS, Lead-free, Mercury Free
- Recyclable packaging material: 100 %

Ergonomics

Swivel	0 °
Tilt	-5/+20 °
Vesa Wallmount	100x100

Power details

Powersupply	Internal
Powersource	100 - 240V 50/60Hz
Power Consumption	On 18.54 watt, Off 0.13 watt Standby 0.29 watt,

Dimensions

Product Dimensions (incl base)	565.4x403.05x219.3 mm
Product Dimensions (excl base)	565.4x342.9x52.95 mm
CartonDimensions	621x476x131 mm
Net Weight (excl package)	4.64
Gross Weight (incl package)	6.1

Warranty

WarrantyPeriod	3 Years
EAN	4038986145213
MTBF	50.000 hours

Regulations

TCO 6,
--------